



FORSYTH GLAZING LIMITED

30 Tobago Street, Glasgow G40 2RH T. 0141 554 0011 F. 0141 554 0088
E. sales@forsythglazing.co.uk www.forsythglazing.co.uk



MORE THAN JUST GLASS

SLIDING DOORS - DATA SHEET

Doors are supported on bottom adjustable wheels.
Top wheels guide the door and assist in smooth running

Measurement

- [1] Measure the width in 3 places - note the “largest dimension”
- [2] Measure the height in 3 places – note the “smallest dimension”

Tolerance

- [1] Door adjustment can accommodate a variance of 20mm in the width of the frame opening size
- [2] The top track can accommodate a variance of 12mm in the height of the frame opening size
- [3] If the opening sizes of the frame are out with these tolerances the frame will need altered

Tracks

- [1] Tracks are supplied cut to length
- [1] Top track is 85mm wide, with pre-drilled fixing holes at 460mm centres
- [2] Bottom track is 57mm wide, not pre-drilled. Holes to be drilled on site
- [3] Outside face of the bottom track to be set back 25mm from the outside face of the top track.
- [4] If using a board for the bottom track it should be no less than 100mm wide.

Safety Anti Jump Clip

- [1] There is a blue flag on each bottom wheel assembly. Rotate this through 90 degrees, push down into track and rotate back. This locks the bottom wheels/door into the track so it cannot jump off.

Glass Products

4mm Mirror and Lacobel [painted glass] which are fitted with an AGC SAFE backing film meet the requirements for classification 2B2 under EN 12600