

SPLASHBACK FITTING

ADVICE

- [1] QUALITY/COLOUR/SIZE – PLEASE CHECK PRIOR TO FITTING**

- [2] SILICONE - ONLY USE LOW MODULUS NEUTRAL CURE CLEAR SILICONE, AS SUPPLIED BY US. WE CANNOT GUARANTEE THAT ANY OTHER ADHESIVE WILL NOT REACT WITH THE PAINT**

- [3] SILICONE - APPLY IN STAGGERED VERTICAL LINES, NOT BLOBS**

- [4] WALLS - PLASTERWORK/ JOINTS SHOULD BE PRIMED/SEALED WITH EMULSION PAINT OR A SUITABLE PVA SOLUTION**

- [5] SOCKETS - APPLY ADEQUATE SILICONE TO SUPPORT GLASS & AVOID GLASS/METAL CONTACT**

- [6] LIGHTER COLOURED SPLASHBACKS – PAINT WALLS WHITE**

- [7] TILES – REMOVE PRIOR TO FITTING SPLASHBACKS**

- [8] PAINTERS CAULK – AVOID AS IT MAY REACT WITH THE PAINT**

WE CANNOT BE HELD LIABLE FOR ANY PAINT / ADHESIVE REACTION WHICH MIGHT OCCUR IF YOU DO NOT ADHERE TO THESE INSTRUCTIONS

IF YOU HAVE ANY QUERIES PLEASE CALL

OUR OFFICE PRIOR TO FITTING

T. 0141 554 0011
F. 0141 554 0088
W. www.forsythglazing.co.uk
SALES. sales@forsythglazing.co.uk
f @ [@forsythglazing](https://www.instagram.com/forsythglazing)

Forsyth Glazing Ltd.
30 Tobago Street, Glasgow G40 2RH



EST. 1969